Page 1

NOTE: The application / location for the materials indicated is not limited to the list below and is to be used in conjunction with and may be supplemented by, the Specifications, Schedules and Drawings. Refer to Specifications, Schedules and Drawings for full extent of material application and additional material types.

CODE ITEM DESCRIPTION APPLICATION / LOCATION

DIVISION 03 - CONCRETE

PNL-1	Cast in Situ concrete knee wall	150mm thk cast in situ concrete with architectural finish and associated pattern details –see A30-00 & A30-01	Exterior Wall Finish
AS-1	Tactile Anti-Slip Inserts	Manufacturer: Urban Access Solutions Product: Tactile Indicators Type: UAS-SS3512.2 Size: 35mm outside diameter	Tactile Walking Surface Indicators (Truncated Domes) Exit stair landings
AS-2	Anti-Slip Inserts	Manufacturer: KN Crowder Product: Stair Nosing Type: CT-20/3 Size: 760mm D x 6.35mm H Color: Extruded Aluminum	Exit stair treads

DIVISION 06 - WOOD, PLASTICS AND COMPOSITES

PLAM1	Plastic Laminate	Manufacturer: Formica	Millwork
		Product: 8845-58	
		Color: Bleached Legno	
		Finish: Matte finish	
PLAM2	Plastic Laminate	Manufacturer: Formica	Counter tops for multi-use
		Product: White Xabia	room and kitchenette in staff area.
		Color: P-311 CA	
		Finish: Matte finish	
WD-1	Solid Wood	Material: maple	Window sill
		Finish: stained	

NOTE: The application / location for the materials indicated is not limited to the list below and is to be used in conjunction with and may be supplemented by, the Specifications, Schedules and Drawings. Refer to Specifications, Schedules and Drawings for full extent

of material application and additional material types.

CODE ITEM DESCRIPTION APPLICATION / LOCATION

DIVISION 07 – THERMAL & MOISTURE PROTECTION

INS-1	Insulation	152mm Polyiso Insulation	Insulation- Roof (min R-40)
INS-2	Insulation	91mm Extruded polystyrene foam insulation (Dow cavity mate ultra or similar)	Insulation- Exterior Walls (min R-20)
INS-3	Insulation	75mm Rigid extruded polystyrene foam insulation	Insulation – below slab on grade for distance of 600mm from perimeter foundation walls (min R- 15)
		50mm Rigid extruded polystyrene foam insulation	Insulation – below grade at perimeter foundation walls from u/s of slab to top of footing (min R-10)
INS-4	Insulation	250mm mineral wool insulation (Roxul or similar)	Insulation – above ceiling in existing building connection (min. R-40)
R-1	SBS Modified Roofing	Cap Sheet on Base Sheet on Tapered insulation to roof drains 2 nd Layer Insulation INS-1 1 st Layer Insulation INS-1 Vapour Barrier 13mm sheathing Structural steel deck	
R-2	SBS Modified Roofing + Precast Pavers	R-1 + Precast Concrete Pavers 600mm x 600mm on Adjustable Pedestals	
PNL-2	Glass Fibre Reinforced Concrete Panel	Manufacturer: James Hardie Product: Hardie Panel Smooth Color: Arctic White Size: 8mm x 1219mm x 2438mm Fasteners: Exposed, Pre-finished to match PNL-2 Accessories: Fry Reglet fibre cement trim accessories or similar	Exterior Wall Finish

NOTE: The application / location for the materials indicated is not limited to the list below and is to be used in conjunction with and may be supplemented by, the Specifications, Schedules and Drawings. Refer to Specifications, Schedules and Drawings for full extent of material application and additional material types.

CODE ITEM DESCRIPTION APPLICATION / LOCATION

PNL-3	Stool pladding	Manufacturer: Vicwest	Exterior Wall Finish
PNL-3	Steel cladding Wall Panel		Exterior Wall Finish
		Product: Prefinished AD300 Horizontal	
		Color: TBC	
		Size: 300mm x 40mm	
		Fasteners: Hidden	
PNL-4	Aluminum Wall Panels	Pre-finished, Colour Anodized to match exterior window frames- black	Exterior Wall Finish
		Fasteners: Exposed, Pre-finished to match PNL-4	
S-1	Glass Fibre	Manufacturer: Certainteed	underside of all roof and canopy
	Reinforced Concrete Panel	Product: Cedar soffit	overhangs
		Color: Cedar	
		Size: 300m/400mm/600mm (to suit soffit size) x 3660mm x 6mm	
		Exposed fixings with cover to match panel	
		Accessories: Fry Reglet fibre cement trim accessories or similar	
EJ1	Expansion Joint	Manufacturer: Allway Standard Metal Floor Covers	Ground floor – proposed slab on grade connection to existing slab
		Product: RFD100	at lobby area.
		Finish: Aluminium	At trafficked areas only.
		Size:238mm	Joint between slab and existing ground floor walls (ie. Non
		Joint width: 25mm	trafficked areas) to be caulked
		Min opening:19mm	appropriately.
		Max opening:51mm	Application: Floor to floor
EJ2	Expansion Joint	Manufacturer: Allway Standard Metal Floor Covers	Second floor – proposed floor slab connection to existing slab at
		Product: RFD200	lobby area.
		Finish: Aluminium	At trafficked areas only.
		Size:238mm	Application: Floor to floor
			Supply and install fire barrier as

Page 4

NOTE: The application / location for the materials indicated is not limited to the list below and is to be used in conjunction with and may be supplemented by, the Specifications, Schedules and Drawings. Refer to Specifications, Schedules and Drawings for full extent of material application and additional material types.

CODE	ITEM	DESCRIPTION	APPLICATION / LOCATION

		Joint width: 51mm	specified in section 079513
		Min opening:19mm	
		Max opening:102mm	
Гю	Evenesian laint	1 0	
EJ3	Expansion Joint	Manufacturer: Allway Standard Metal Floor Covers	Second floor – proposed floor slab connection to existing second floor
		Product: RFWD200	walls at lobby area.
		Finish: Aluminium	At non trafficked areas only.
		Size:238mm	Application: Floor to wall
		Joint width: 51mm	Supply and install fire barrier as specified in section 079513
		Min opening:19mm	•
		Max opening:102mm	
EJ4	Expansion Joint	Manufacturer: Situra	Roof level – proposed roof to
		Product: Flamline	existing roof level walls
		Type: Elastomeric expansion joint	Application: roof to wall
		Opening: To accommodate +/-50mm	
EJ5	Expansion Joint	Manufacturer: Emseal	Ground floor to second level –
		Product: Emseal Seismic Colorseal	vertical joint between existing walls and proposed walls
		Finish: Silicone coated	Application: wall to wall
		Size:60mm	
		Joint width: 60mm	
		Min opening:30mm	
		Max opening:90mm	
EJ6	Expansion Joint	Manufacturer: Emseal	Second floor to roof level- vertical
		Product: Emseal Seismic Colorseal	joint between existing walls and proposed walls
		Finish: Silicone coated	Application: wall to wall
		Size:100mm deep	.,
		Joint width: 100mm	
		Min opening:50mm	
		Max opening:150mm	

DIVISION 08 - OPENINGS

NOTE: The application / location for the materials indicated is not limited to the list below and is to be used in conjunction with and may be supplemented by, the Specifications, Schedules and Drawings. Refer to Specifications, Schedules and Drawings for full extent of material application and additional material types.

CODE	ITEM	DESCRIPTION	APPLICATION / LOCATION

GL-T	Tempered Glass, Clear	Manufacturer: Elegant Aluminum Canada	Terrace
		Product: GP-Premier Line Glass Railing full view 2 channel	
		Color: Black	
		Size: 1070mm high x length to suit plans	
		Fasteners: Exposed	
GL-W	Interior Fire Rated –Wired Glass	Rating: 45min.	Doors in Rated Walls at stairs See A02-00
GL-L-1	Sidelights	Glass Clean Laminate glass	Sidelights
		Color: Clear	
		Size: 12 mm glass	
ROL-1	Steel counter door	Product: FPC Steel Counter Door, rugged 2" flat slats	
		Manufacturer: Service Door industries limited	
		Options: Crank operation	
		Finish: Powder coat finish	
		Color: TBD	

DIVISION 09 - FINISHES

TRM-1	Tile Trim	Manufacture: Schluter Style: QUADEC/-K Finish: Stainless Steel	Finishing edge-protection on outside corners within washrooms and other wall tiled areas.
TRM-2	Floor Trim	Manufacture: Schluter Style: RENO-RAMP/-K	Between carpet and concrete floor
		Finish: Stainless Steel	
CONC	Sealed Concrete	Manufacturer: On-site	Throughout
TRZ1	Terrazzo shower	Product: Poured Terrazzo	Poured Terrazzo for shower base.

NOTE: The application / location for the materials indicated is not limited to the list below and is to be used in conjunction with and may be supplemented by, the Specifications, Schedules and Drawings. Refer to Specifications, Schedules and Drawings for full extent of material application and additional material types.

CODE ITEM DESCRIPTION APPLICATION / LOCATION

	h	T	Fitte Ottoma Oite Onideline
	base	Color: to match wall tiles (TBD)	Fit to Ottawa City Guidelines barrier free shower.
		Size: 1500mm X 1049mm,	
		Threshold height: Max. 13mm	
		Base splash height: max. 100mm	
CPT1	Carpet Hexagon	Manufacturer: Shaw Contract	Library and staff area only – 50%
	Tile	Style Name: Linear Hexagon	Contact: Deanne Duncan
		Style No: 5T055	Shaw Industries
		Color: Charcoal – 55595	3284 Leroy St. Osgoode, ON
		Installation: Random	613-294-0000
			Deanne.duncan@shawinc.com
CPT2	Carpet Hexagon	Manufacturer: Shaw Contract	Library and staff area only - 40%
	Tile	Style Name: Linear Shift Hexagon	Contact: Deanne Duncan
		Style No: 5T056	Shaw Industries
		Color: Charcoal Tweed – 56595	3284 Leroy St. Osgoode, ON
		Installation: Random	613-294-0000
			Deanne.duncan@shawinc.com
СРТ3	Carpet Hexagon	Manufacturer: Shaw Contract	Library area accent – 10%
	Tile	Style Name: Plane Hexagon	Contact: Deanne Duncan
		Style No: 5T054	Shaw Industries
		Color: Chartreuse - 54325	3284 Leroy St. Osgoode, ON
		Installation: Random	613-294-0000
			Deanne.duncan@shawinc.com
PAV1	Concrete Paver	Size: 600mm x 600mm x 50mm	Entrance walkway & terrace
	Tile		
GYP	Gypsum Drywall		
POR1	Porcelain Tile	Supplier: Olympia Tile	Universal washroom and public
		Product: Color and Dimension	washroom.
		Collection – Group 1	Contact:
		Color: Warm White Matte	Sophie Janney

NOTE: The application / location for the materials indicated is not limited to the list below and is to be used in conjunction with and may be supplemented by, the Specifications, Schedules and Drawings. Refer to Specifications, Schedules and Drawings for full extent of material application and additional material types.

CODE ITEM DESCRIPTION APPLICATION / LOCAT

		T	I
		Finish: matte	Olympia Tile
		Size: 8x20 (200mm x 505mm)	Tel: 613-736-9570 ext. 217
		Code: QT.CD.WWT.0820.MT	Sophie.olympiatile@bellnet.ca
			2480 Don Reid Dr. Ottawa, ON
GRT1	Grout	Product: ARDEX grouts	Grout for wall porcelain tile in
		Color: Polar White – 01	universal washroom and public washroom.
		Thickness: 3mm	
PT-1	Paint	Manufacturer: Benjamin Moore	General wall finish
	General	Color: White Opulence	
		Code: OC-69	
		Sheen: eggshell	
PT-2	Paint	Manufacturer: Benjamin Moore	Accent paint
	Accent	Color: Cape Hatteras Sand	
		Code: AC-34	
		Sheen: eggshell	
PT-3	Paint	Manufacturer: Benjamin Moore	General door and frame paint
	Door + frame	Color: Ashley Grey	
		Code: HC-87	
		Sheen: semi-gloss	
PT-4	Paint	Manufacturer: Benjamin Moore	Door and Frame paint in Library -
	Door + Frame	Color: Chelsea Grey	Staff area
		Code: HC-168	
		Sheen: semi-gloss	
PT-5	Painted exposed	Manufacturer: Benjamin Moore	All exposed areas without ceilings
	steel deck/beams/	Color: White Opulence	lobbies, stairs, Fitness Centre, storage
	mech equip	Code: OC-69	storage
		Sheen: eggshell	
WB-1	Rubber Base	Manufacturer: Johnsonite	All areas that have Carpet will
		Style Name: Rubber base	receive rubber base
		Style No: Tight lock carpet base	

NOTE: The application / location for the materials indicated is not limited to the list below and is to be used in conjunction with and may be supplemented by, the Specifications, Schedules and Drawings. Refer to Specifications, Schedules and Drawings for full extent of material application and additional material types.

CODE ITEM DESCRIPTION APPLICATION / LOCATION

		Color: 68 White Sand	
		Size: 3mm x 100mm	
WB-2	Porcelain Base	Supplier: Olympia Tile	Universal washroom and public
		Product: Color and Dimension Collection – Group 1	washroom. Contact:
		Color: Warm White Matte	Sophie Janney
		Finish: matte	Olympia Tile
		Size: 8x20 (200mm x 505mm)	Tel: 613-736-9570 ext. 217
		Code: QT.CD.WWT.0820.MT	Sophie.olympiatile@bellnet.ca
			2480 Don Reid Dr. Ottawa, ON
C-1	Acoustical Ceiling Tile	Manufacturer: Armstrong	Library and Multi-purpose room
		Product: Cortega Lay-in 769	Contact:
		Color: White	Roger Richer
		Edge Detail: Square Lay in	rpricher@armstrong.com
		Size: 610mm x 1220mm x 15.8mm	613-852-2791
		Grid: Prelude ML 15/16" Exposed Tee	
		NRC: 0.55	
C-2	Suspended Gypsum Drywall		Washrooms, Vestibule
AH1	Access Hatches	Manufacturer: Cendrex	Access hatches –Drywall Installation.
		Product: CTR	
		Type: Access Door with Hidden Flange	
		Size: 355mm x 355mm	

DIVISION 10 - SPECIALTIES

NOTE: The application / location for the materials indicated is not limited to the list below and is to be used in conjunction with and may be supplemented by, the Specifications, Schedules and Drawings. Refer to Specifications, Schedules and Drawings for full extent of material application and additional material types.

CODE	ITEM	DESCRIPTION	APPLICATION / LOCATION

PTN1	Washroom Partitions	Manufacturer: Bobrick Product: High Pressure Laminate Classic Series 1541 Mounting: floor anchored Finish: laminate - Formica	Toilet Compartments
		Colour: Bleached Legno 8845-58	
PTN2	Urinal Partitions	Manufacturer: Bobrick	Urinals
		Product: High Pressure Laminate Classic Series 1545	
		Mounting: Wall hung	
		Finish: Laminate - Formica	
		Colour: Bleached Legno 8845-58	

DIVISION 12 – FURNISHING

FAB-1	Roller Blinds	Manufacturer: Sun Glow	Fitness Centre
		Series: Manual NEO Chainless Safety Shade	
		Fabric: SG Sunscreen CS-103	
		3% openness in White	
FAB-2	Roller Blinds	Manufacturer: Sun Glow	Multipurpose room, lobbies, library
		Series: Manual Neo Chainless Safety Shade	
		Fabric: SG Sunscreen CS-103	
		3% openness in white	
MAT	Entrance Mat	Manufacturer: 3M	At vestibule
		Product: Nomad 8150 Backed Scraper Matting (Heavy Traffic)	
		Finish: Grey	
		Size: 1220mm x 1828mm	

END OF DOCUMENT